



Foto on esinduslik



Eaton 5E900UD

Eaton 5E Gen2 UPS USB DIN, 900 VA, 480 W,
Input: Schuko, Outputs: (2) DIN, Tower

Üldised spetsifikatsioonid

PRODUCT NAME	Eaton 5E Gen2 UPS
CATALOG NUMBER	5E900UD
EAN	3553340704246
PRODUCT LENGTH/DEPTH	288 mm
PRODUCT HEIGHT	148 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	5.27 kg
COMPLIANCES	CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC Ukr IEC/EN 62040-3 UKCA Cm

Backup power conversion specifications

SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design
- HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)
- Includes two Schuko (DIN) Outlets

Nominal output voltage specifications

OUTPUT NOMINAL VOLTAGE	230V
------------------------	------

Single-phase UPS specifications

BATTERY QUANTITY	1
EFFICIENCY AT MAX. LOAD	95
INPUT VOLTAGE RANGE	140-300 V
OUTPUT FREQUENCY	50/60 Hz
OUTPUT VOLTAGE RANGE	195-257 V
PHASE (INPUT)	1
PHASE (OUTPUT)	1

Input nominal voltage specifications

INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
-----------------------	--------------------------------

Office residential UPS specifications

INPUT VOLTAGE - MAX	300 V
INPUT VOLTAGE - MIN	140 V
OPERATING TEMPERATURE - MAX	40 °C
OPERATING TEMPERATURE - MIN	0 °C
OUTPUT APPARENT POWER	900 VA
OUTPUT VOLTAGE - MAX	257 V
OUTPUT VOLTAGE - MIN	195 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz

UPS battery specifications

BATTERY MANAGEMENT	Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	No
RUNTIME GRAPH	\$row.attributeValue.cdata

Katkematu toite allika andmeside spetsifikatsioonid

COMMUNICATION	USB port (HID compliant)
ETHERNET INTERFACE	No
EXPANSION SLOTS	No
INCLUDES NETWORK CARD	No
POTENTIAL FREE SWITCH CONTACT	No
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
TYPE OF INTERFACE	USB
USER INTERFACE	LEDs

UPS general specifications

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
CONSTRUCTION TYPE	Free standing model
HOT SWAP POWER	No
INTERNAL BYPASS	No
PACKAGE CONTENTS	• Quick start • Safety instructions
PRIMARY FREQUENCY - MAX	63 Hz
PRIMARY FREQUENCY - MIN	45 Hz
RACK MOUNTING KIT	No
SURGE PROTECTION	Yes
TOPOLOGY	Line-interactive
VA RATING	850 VA
WATTAGE	480 W

UPS environmental specifications

RELATIVE HUMIDITY	0-90% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

UPS input specifications

INPUT CONNECTION	Protective contact (SCHUKO)
INPUT CORD LENGTH	1.2 m
INPUT FREQUENCY RANGE	45-63 Hz
NOMINAL FREQUENCY	50/60 Hz

UPS output specifications

FEED TYPE	1
NUM OF OUTPUTS PC (SCHUKO)	2
RECEPTACLE	(2) Schuko
VOLTAGE	230V
VOLTAGE TYPE	AC

Abiinfo

PROJEKTI NIMI:
PROJEKTI NUMBER:
KOOSTAJA:
KUUPÄEV:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Iirimaa
Eaton.com

© 2026 Eaton. Kõik õigused on kaitstud.

Jälgige meid sotsiaalmeedias, et saada uusimat toote- ja tooteavet.

