

Eaton 5P650IR

Eaton 5P UPS, 650 VA, 420 W, Input: C14,
Outputs: (4) C13, Rack, 1U



Foto on esinduslik



Üldised spetsifikatsioonid

PRODUCT NAME	Eaton 5P UPS
CATALOG NUMBER	5P650IR
PRODUCT LENGTH/DEPTH	364 mm
PRODUCT HEIGHT	43.2 mm
PRODUCT WIDTH	438 mm
PRODUCT WEIGHT	8.6 kg
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE EAC cTUVus

Battery

RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection
BATTERY REPLACEMENT	User replaceable
BATTERY QUANTITY	1
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Lead-acid maintenance-free (replaceable)
EXTENDED BATTERY CAPABILITY	No

Electrical input

INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
INPUT VOLTAGE RANGE	160-294 V (adjustable to 150 V-294 V)
NOMINAL FREQUENCY	50-60 Hz
INPUT FREQUENCY RANGE	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

Electrical output

RECEPTACLE	(4) C13
TOPOLOGY	Line-interactive
WATTAGE	420 W
VA RATING	650 VA
OUTPUT WAVEFORM	Sine wave
VOLTAGE	230V
OUTPUT POWER FACTOR	0.65
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
OUTPUT VOLTAGE RANGE	230 V (+6%/-10%)
OUTPUT FREQUENCY	50/60 Hz
FEED TYPE	1

Communications

COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini-terminal block for remote On/Off and Remote Power Off
- Dry contacts (2 outputs, optocoupler, RJ)

EXPANSION SLOTS	One slot for optional communication card
ETHERNET INTERFACE	No
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
USER INTERFACE	Multilingual graphical LCD display
TYPE OF INTERFACE	Other
POTENTIAL FREE SWITCH CONTACT	Yes

Environmental

ALTITUDE	2000 m
BTU RATING	Online: 85
NOISE LEVEL	<40 dB at 1 meter
RELATIVE HUMIDITY	0-90% non-condensing
TEMPERATURE RANGE	0-90% non-condensing

Additional specifications

- Automatic Voltage Regulation (AVR)
- High-density protection for networks: 1U only
- Energy efficient, reduce energy and cooling costs
- Delivers clean sinewave output
- 1 slot for optional com card (Network management card, Relay card or Network and Industrial card)
- Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)
- Fully integrates with Eaton Intelligent Power Manager software
- 1 USB port + 1 serial port
- Advanced Battery Management (ABM) technology to increase battery lifetime
- Next-generation graphical LCD display
- Hot swappable batteries
- Remote reboot and runtime optimization thanks to 2 manageable outlet groups

SPECIAL FEATURES

RACK SIZE	1U
CONSTRUCTION TYPE	482.6 mm (19 inch) device
ENCLOSURE	Black/silver
RACK MOUNTING KIT	Yes
EFFICIENCY AT MAX. LOAD	96

- | | |
|-------------------------|--|
| PACKAGE CONTENTS | <ul style="list-style-type: none">• Rack-mounting kit• Cable locking system |
|-------------------------|--|

- USB cable
- Serial cable
- (2) IEC-IEC cables
- Quickstart guide
- Safety instructions
-

PHASE (INPUT)	1
PHASE (OUTPUT)	1
AUTO SHUTDOWN FUNCTION	Yes

Abiinfo

PROJEKTI NIMI:

PROJEKTI NUMBER:

KOOSTAJA:

KUUPÄEV:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Iirimaa
Eaton.com

Jälgige meid sotsiaalmeedias, et
saada uusimat toote- ja tooteavet.



© 2026 Eaton. Kõik õigused on kaitstud.